

TECHNO ADHESIVES COMPANY

12113 Mosteller Road
Cincinnati, Ohio 45241

Phone: (513) 771-1584
1-800-432-0107

Fax: (513) 771-1684
www.technoadhesives.com

**TECHNO ADHESIVE NO. 155 AEROSOL
WEB SPRAY FLEXIBLE FOAM ADHESIVE**

BASE: Synthetic Elastomer

DESCRIPTION: This is a spray applied flexible foam cement for bonding all types of foams to themselves and various substrates, such as cloth, wood, or metal. It has excellent application characteristics including quick tack, high coverage and high strength bonds. It produces soft non-dimpling bonds which will not harden or darken with age. Fabrics in contact with this bond line will not become stained after aging for long periods even when exposed to sunlight.

CAUTION: This cement is flammable. Keep away from sparks and open flames. Provide adequate ventilation.

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed, it being specifically understood that there are no warranties either expressed or implied incident to the sale of this product. No person is authorized or empowered to make any statement or recommendation concerning said product not contained herein, and any such statement or recommendation so made shall not bind the company. Users assume all risk and liability whatsoever resulting from the use of this product and must confirm the adaptability thereof by their own tests.